



TECHNICAL DATA SHEET FOR STANDARD MOBILE TANKS / FICHE TECHNIQUE DES RÉSERVOIRS MOBILES STANDARDS

Complies with / Conforme à: UN 31A/CGSB43.146-2016



Item #	Volume			Type	Épaisseur/ Thickness	Poids Tare / Tare Weight		Poids plein / Full weight		Dim hors tout / All out dims		
	L	Gal. Imp	Gal. US			Kg	Lbs	Kg	Lbs	L (po)	I (po)	H (po)
AGB-TANK0200SW	200	44	53	Simple paroi / Single wall	11 ga	76.4	168	282.7	622	47 3/8	20 1/4	21 1/2
AGB-TANK0200SW-R	200	44	53	Simple paroi / Single wall	12ga	63	139	263	579	45 1/4	21	21 1/2
AGB-TANK0200LC	200	44	53	Simple paroi / Single wall	12 ga	18	39	218	479	48	34 1/4	25 3/4
AGB-TANK0200DW	200	44	53	Double paroi / Double wall	12 ga (in) - 12 ga (out)	134.1	295	334.1	735	48	21 1/4	22
AGB-TANK0200DW-TL	200	44	53	Double paroi / Double wall	10 ga (top) 12 ga (in) 12 ga (out)	193	424	393	864	36	24	39 1/16
AGB-TANK0300SW	300	66	79	Simple paroi / Single wall	11 ga	93.6	206	39.5	879	47 3/8	24 3/4	24 1/4
AGB-TANK0300SW-R	300	66	79	Simple paroi / Single wall	12ga	81	178	381	838	46	29	22 1/2
AGB-TANK0300DW	300	66	79	Double paroi / Double wall	12 ga (in) - 12 ga (out)	187.3	412	487.3	1072	48	25 1/4	25 3/4
AGB-TANK0320LC (48")	320	70	85	Simple paroi / Single wall	12 ga	170	374	490	1078	51 1/4	31 1/4	28 1/2
AGB-TANK0320LS (48")	320	70	85	Simple paroi / Single wall	12 ga	118	260	438	964	51 1/4	31 1/4	28 1/2
AGB-TANK0450SW	450	99	119	Simple paroi / Single wall	11 ga	116.4	256	566.4	1246	47 3/8	32 1/2	26
AGB-TANK0450SW-R	450	99	119	Simple paroi / Single wall	12 ga	103	226	553	1217	46	38	23 7/8
AGB-TANK0450LC	450	99	119	Simple paroi / Single wall	12 ga	200	439	650	1430	51 1/4	38 1/8	28 1/2
AGB-TANK0450LS	450	99	119	Simple paroi / Single wall	11 ga	256	564	706	1554	51 1/4	38 1/8	26 7/16
AGB-TANK0450DW	450	99	119	Double paroi / Double wall	12 ga (in) - 12 ga (out)	207.3	456	657.3	1446	48	34 3/8	26 3/16
AGB-TANK0450DW-TL	450	99	119	Double paroi / Double wall	10 ga (top) 12 ga (in) 12 ga (out)	321	706	771	1696	58	30	48 1/4
AGB-TANK0600SW	600	132	159	Simple paroi / Single wall	3/16	219.5	483	819.5	1803	60 1/2	35 3/8	26
AGB-TANK0600DW	600	132	159	Double paroi / Double wall	11 ga (in) - 12 ga (out)	262.7	578	862.7	1898	60 1/2	30 1/4	30 7/8
AGB-TANK0800SW	800	176	211	Simple paroi / Single wall	3/16	260.9	574	1060.9	2334	59 3/4	36 3/8	32 1/2
AGB-TANK0800DW	800	176	211	Double paroi / Double wall	11 ga (in) - 12 ga (out)	320.9	706	1120.9	2466	60 1/2	37 1/4	32 3/8
AGB-TANK0800DW-TL	800	176	211	Double paroi / Double wall	3/16 (Top) 11 ga (in) 12 ga (out)	547	1204	1347	2964	59	44	51 9/16
AGB-TANK1000SW	1000	220	264	Simple paroi / Single wall	3/16	294.1	647	1294.1	2847	60 1/2	44 3/8	32 1/8
AGB-TANK1000DW	1000	220	264	Double paroi / Double wall	11 ga (in) - 12 ga (out)	364.5	802	1364.5	3002	60 1/2	45 1/4	32 1/4
AGB-TANK1000DW-TL	1000	220	264	Double paroi / Double wall	3/16 (Top) 11 ga (in) 12 ga (out)	573	1260	1573	3460	60 1/2	45 1/4	56 1/16
AGB-TANK2000UN	2000	440	528	Simple paroi / Single wall	3/16	497	1094	2497	5494	92	44 1/8	41
AGB-TANK2000HD	2000	440	528	Haute Résistance / Heavy duty	1/4	630	1386	2630	5786	92	44 1/8	41
AGB-TANK2000DW	2000	440	528	Double paroi / Double wall	3/16 (in) - 12 ga (out)	734	1615	2734	6015	92	46 1/2	39 11/16
AGB-TANK2000DW-TL	2000	440	528	Double paroi / Double wall	3/16 (Top) 3/16 (in) 12 ga (out)	996	2191	2996	6591	76	47 1/2	68 3/16
AGB-TANK3000SW	3000	660	793	Simple paroi / Single wall	1/4	862	1897	3862	8497	92	50 1/4	51 1/2
AGB-TANK3000DW	3000	660	793	Double paroi / Double wall	1/4 (in) - 12 ga (out)	1220	2685	4220	9285	93 3/4	50 1/4	52
AGB-TANK4500SW	4500	990	1189	Simple paroi / Single wall	1/4	1127	2479	5627	12379	92 3/4	59 3/4	62 1/2
AGB-TANK4500DW	4500	990	1189	Double paroi / Double wall	1/4 (in) - 12 ga (out)	1590	3498	6090	13398	92 3/4	60 1/2	63 1/4
AGB-TANK5000SW	5000	1100	1321	Simple paroi / Single wall	1/4	1193	2625	6193	13625	92	65 3/8	63 1/4
AGB-TANK5000DW	5000	1100	1321	Double paroi / Double wall	1/4 (in) - 12 ga (out)	1698	3736	6698	14736	92 3/4	65 3/4	63 3/4